



# 1118 ELASTAKOTE

## 100% Acrylic Elastomeric Coating

### Product Description

A premium quality, exterior, 100% acrylic smooth elastomeric coating. Features waterproofing properties, good film strength, elasticity, elongation and bridging of hairline cracks. Designed for above grade concrete, concrete block, stucco, and masonry. Suitable for **incidental** use on primed wood and metal. Excellent for commercial and residential application.

### Compliance - Performance - Certification

- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

### Performance Features

- **Durable**
- **Weather Resistance**
- **Bridges Hairline Cracks**
- **Prevents Moisture Penetration**
- **Highly Flexible**
- **300% Elongation**
- **Water Clean-up**

### Product Specifications

Resin Type	Acrylic
Color Range	White & custom tinted colors
Finish	Flat <3 @ 60° (MPI Gloss Level 1)
Drying Time (75° F. & 50% R.H.)	To touch: 2 hours To recoat: 24 hours
Practical Coverage	Approx. 80-100 sq ft/gallon
Recommended Dry Film Thickness	8-10 mils per coat
Weight Per Gallon	10.5 lbs.
Solids By Weight	60%
Solids By Volume	50%
Water Vapor Permeance	12 Perms @ recommended dry film thickness
Shelf Life	2 years (unopened containers)
Sizes	One & five gallon containers
V.O.C.	<50 Grams per liter
Clean Up	Water.

### Product Analysis (by weight)

PIGMENT COMPOSITION		28%
Titanium Dioxide:		6%
Silicates:		20%
Calcium Carbonate:		2%
VEHICLE COMPOSITION		72%
Acrylic Resin:		31%
Water, Surfactants, Defoamers:		41%

### Surface Preparation

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, glazed or dense surfaces. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

### Previously Painted Surfaces:

Spot prime bare or patched areas or prime entire surface, as required. Prime lightly-chalked painted surfaces with a suitable Kelly-Moore Surface Conditioner. Loose paint and medium to heavy chalk must be removed.

### System Recommendations

#### Concrete, Stucco & Masonry

PRIMER: 247 Acry-Shield 100% Acrylic  
Masonry Primer

OR 98-001 Stucco Seal

FINISH: 2 Coats 1118 Elastakote Acrylic  
Elastomeric Coating

*Continued Next Page*

# 1118 ELASTAKOTE (cont.)

---

## Incidental Wood & Hardboard:

PRIMER: 255 Acry-Shield 100% Acrylic  
Wood Primer

## Incidental Metal (ferrous, galvanized, or aluminum):

PRIMER: 1725 Acry-Shield 100% Acrylic  
Metal Primer

FINISH: 1118 Elastakote Acrylic Elastomeric  
Coating

## Application:

Brush, roll, or spray. Avoid lap marks by maintaining a wet edge at all times. Apply a full, even coat. Two coats are required for optimum performance. Do not apply when material, air, and/or surface temperature is below 50° F. or when rain is expected within 72 hours.

In order to achieve a waterproof wall, the coating must be applied in a continuous unbroken film, free of pinholes and voids. When sprayed on rough or porous surfaces, back-rolling procedure is recommended to fill holes more efficiently.

**This product must be applied at the recommended film thickness to achieve proper cure.**

## Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

## Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION  
KEEP OUT OF REACH OF CHILDREN.

## Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

**Mildew:** This paint has been formulated to be mildew resistant, however, it will not mildew-proof the surface nor completely prevent or destroy mildew. Therefore, Kelly-Moore Paint Company Inc. assumes no responsibility for mildew development.

**Limited Warranty:** The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.