



117 - 332

## Latex Pallet Paint

### Product Description

A waterborne, anti-microbial paint for marking pallets.

### Performance Features

- Quick drying
- Can be applied by brush, roller or spray
- Water clean-up

### Product Specifications

|                                     |  |
|-------------------------------------|--|
| Resin Type:                         | Vinyl Acrylic                                |
| Color Range:                        | Red  |
| Finish:                             | 10-20 @ 85°                                  |
| Drying Time:<br>(75° F. & 50% R.H.) | To touch: 30-60 min.<br>To recoat 2-4 hours. |
| Practical Coverage:                 | 200-350 sq. ft./Gallon                       |
| Recommended Dry<br>Film Thickness   | 1.5-2.5 mils per coat                        |
| Weight Per Gallon:                  | 9.9 lbs.                                     |
| Solids By Weight:                   | 45%  |
| Solids By Volume:                   | 34%  |
| Shelf Life:                         | 2 years (unopened containers)                |
| V.O.C.                              | <55 Grams per liter                          |
| Clean Up:                           | Water  |

### Product Analysis

This product is manufactured from a variety of virgin and post-manufacturing materials.

### Surface Preparation

**General:** All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating.

### System Recommendations

FINISH: 117-332 Latex Pallet Paint

### Application

Brush, roll or spray. Do not apply when material, air, and/or surface temperature is below 50°F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

### Thinning

May be applied as supplied or thinned with water to desired consistency.

### Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION  
KEEP OUT OF REACH OF CHILDREN.

**Warranty:** This product is sold without warranty. Kelly-Moore Paint Company, Inc. and its distributors assume no responsibility express or implied for use of this product. Suitability of this product for any specific purpose must be determined by the user.