



1287 ENVIRA-CRETE

Acrylic Sealer/Stain

Product Description

A semi-opaque, waterborne, acrylic sealer/stain for concrete surfaces.

Performance Features

- Excellent Weather Resistance
- Excellent Color Retention
- Low Odor & VOC
- Easy Application
- Easy Soap & Water clean-up
- WSDOT QPL

Product Specifications

Resin Type:	Acrylic
Color Range:	Washington Gray
Finish:	Flat <5 @ 60° (MPI Gloss Level 1)
Drying Time: (75° F. and 50% R.H.)	To touch: 1 hour To recoat: 4 hours.
Practical Coverage:	Approx. 250-400 sq ft/gallon
Recommended Dry Film Thickness:	1.5-2.0 mils per coat
Weight per Gallon:	10.7 lbs.
Solids by Weight:	51%
Solids by Volume:	36%
Shelf Life:	2 years (unopened containers)
V.O.C.	<95 Grams per liter
Clean Up:	Water

Product Analysis (by weight)

PIGMENT COMPOSITION		33%
Titanium		3%
Extenders		30%
VEHICLE COMPOSITION		67%
Acrylic Resin:		18%
Water, Surfactants, Defoamers:		49%

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating.

System Recommendations

Concrete:
FINISH: 1287 Envira-Crete

Application

Do not apply when material, air, and/or surface temperature is below 50°F or if rain is imminent. Extremely high or low temperature or periods of high relative humidity may adversely affect dry time. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Continued Next Page

1287 ENVIRA-CRETE (cont.)

Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Prevent spontaneous combustion of spray residues, rags and other waste material contaminated with this product by promptly immersing them in water for disposal. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.