

Product Description

A waterborne semi-transparent stain for exterior or interior use on bare wood surfaces. Features superior UV protection and water repellency. May be used on vertical or horizontal surfaces.

*Conforms to Green Seal Paints GS-11 Criteria
Meets CARB VOC Limits
Meets National AIM VOC Limits*

Performance Features

- Excellent Weather Resistance
- Excellent Color Retention
- Contains Trans-Oxide Pigments
- Allows Texture and Grain to Show
- Nano Technology
- Low Odor & VOC
- May be Applied to Damp Surfaces
- Easy Application
- Easy Soap & Water Clean-up

Product Specifications

Color Range:	700 Clear, 701 Cedar, 702 Western Brown, 703 Redwood, 704 Sierra Brown, 705 Driftwood
Finish:	Near Flat, Penetrating
Drying Time: (75° F. and 50% R.H.)	To touch: 15 minutes Tack Free: 30 minutes.
Practical Coverage (sq. ft. / gallon):	Approx. 150-275 on rough surfaces, 275-375 on smooth surfaces.
Weight per Gallon:	8.40-8.65 lbs..
Solids by Weight:	14-16%
Solids by Volume:	13-16.5%
Shelf Life:	2 years (unopened containers)
Sizes:	One & five gallon containers
V.O.C.	<60 Grams per liter
Clean Up:	Warm Soapy Water

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating. To insure maximum adhesion, the substrate must be free of all dead wood fibers. **Note:** When wood is milled, the process leaves the surfaces of the wood hard and slick. This condition is known as "Mill Glaze". If this condition exists at time of application, it will not allow stains to properly penetrate the surface of the wood. This surface of the wood should be sanded thoroughly to create surface profile. After sanding, wet the wood surfaces with water. Wetting will enhance the porosity of the surfaces to be stained. Stain may be applied to damp surface.

System Recommendations

Wood:

FINISH: 1288 Acry-Shield Exterior Waterborne Semi-Transparent Stain



Application: Brush, Roll or Spray

Do not apply when material, air, and/or surface temperature is below 40°F or above 95°F or if rain is imminent. Extremely high or low temperature or periods of high relative humidity may adversely affect dry time. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks. Avoid applying in direct sunlight.

Caution: This product should not be tinted or thinned.

Continued Next Page

1288 ACRY-SHIELD (cont.)

CAUTION: Kelly-Moore assumes no responsibility whatsoever for variations in color, or color acceptability, after application. Always apply a test sample on wood to be stained prior to application. Color and color intensity will vary depending on the degree of porosity, texture and type of wood. Use care in application because color depth increases rapidly with successive coats and where overlapping occurs. Due to the nature of the product, color uniformity cannot always be maintained from batch to batch.

Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Keep container closed when not in use. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.