



1475 Zone Marking Paint Fast Dry - Low VOC

Product Description

ZONE MARKING PAINT Fast Dry - Low VOC is a zone marking paint designed for application to concrete or asphalt road surfaces, parking lots, driveways, warehouse floors, sidewalks and curbs. It is suitable for use on bituminous and concrete surfaces.

Performance Features

- Fast Dry
- Low VOC
- Excellent Durability
- Low Temperature Application (40° F.)
- Easy Application

Product Specifications (White)

Resin Type:	Acrylic
Color Range:	100 White, 131 Yellow, 132 Red, 134 Black, 135 Blue
Drying Time: (77° F. 50% R.H.)	No pick-up: <10 minutes
Practical Coverage:	320 - 480 feet of 4" stripe/gal.
Recommended Dry Film Thickness:	5.0-7.5 mils per coat
Density:	11.5 lbs.
Solids By Weight:	72%
Viscosity:	70-85 (D562 @ 77° F.)
Fineness of Grind:	3 (Hegman Guage, D1210, 2,5 min.)
Dry Opacity:	0.92 @ 5 mils wet (min.)
Sizes:	Five gallon containers
Flash Point:	<32° F.
V.O.C.	<100 Grams per liter
Clean Up:	Acetone

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating.

Application

Spray equipment, line strippers. Small areas may be rolled with a long nap roller. Do not apply when material, air, and/or surface temperature is below 40°F. Extremely high or low temperature may adversely affect dry time. Mix thoroughly before and during use. When applying glass beads use pressurized bead dispenser for best results.

Thinning

This product is designed to be applied un-thinned under normal environmental and application conditions.

Continued Next Page

Precautions

DANGER! FLAMMABLE LIQUID AND VAPOR VAPORS MAY CAUSE FLASH FIRE

Contains Aliphatic & Aromatic Hydrocarbons.

Flammable. Keep away from heat, sparks and flame. Vapors can travel long distances and may ignite explosively and cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation or by using explosion-proof exhaust fans both during and after application. Prevent spontaneous combustion of spray residues, rags and other waste material contaminated with this product by immediately immersing them in water for disposal.

Vapor Harmful. Do not breathe vapors or spray mist which may affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Wear a properly fitted organic vapor respirator (NIOSH/MSHA TC-23C or equivalent) until fumes are gone or leave the area. Close container after each use. Do not transfer contents to other containers for storage.

First Aid: In case of eye contact, flush with plenty of water for at least 15 minutes and get medical attention if irritation persists. For skin contact, wash thoroughly with soap and water. If affected by vapor inhalation, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get prompt medical attention. If swallowed, call physician immediately. Never give anything by mouth to an unconscious person. **Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

USE ONLY WITH ADEQUATE VENTILATION.
FOR PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.