

THIS PRODUCT MAY NOT BE AVAILABLE IN SOME AREAS DUE TO VOC REGULATIONS
Contact your Kelly-Moore representative for more information

Product Description

A pigmented oleoresinous penetrating semi-transparent wood stain. Designed to color and enrich the natural beauty of wood. Fast drying for use with a complete lacquer or varnish system.

Performance Features

- Penetrates Wood
- Enhances Wood Grain
- Semi-Transparent Finish
- Fast Dry
- Easy Application

Product Specifications

Resin Type:	Alkyd
Color Range:	Custom tints
Drying Time: (75° F. & 50% R.H.)	To topcoat: 1 hour.
Coverage:	Approx. 500-700 sq ft/gallon
Weight per Gallon:	6.7 lbs.
Solids by Weight:	10%
Solids by Volume:	8%
Shelf Life:	2 years (unopened containers)
Sizes:	Quarts
V.O.C.	<750 Grams per Liter
Clean Up:	Mineral Spirits

Product Analysis before tinting (by weight)

PIGMENT COMPOSITION	1%
VEHICLE COMPOSITION	99%
Alkyd Resin:	9%
Solvent, Driers, Additives :	90%

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

System Recommendations

STAIN: 2152 Modern Wood Finish
FINISH: Alkyd Varnish, Lacquer or other compatible clear finish.

Application

Brush, roll or spray. Maintain a wet edge to avoid lap marks. Best results are obtained by wiping stained surface immediately with a soft, dry cloth. Do not apply when material, air, and/or surface temperature is below 40°F. Stir thoroughly before and during use. Always test stain on wood to be stained prior to application. Semi-transparent stains vary significantly depending on color and porosity of substrate as well as application methods. Due to the nature of the product, color uniformity may vary from batch to batch.

Thinning Use at package consistency or, if desired, color depth may be adjusted by reducing with mineral spirits.

Continued Next Page

2152 STAINZ-RITE (cont.)

Precautions

**DANGER! HARMFUL OR FATAL IF SWALLOWED.
FLAMMABLE LIQUID AND VAPOR.**

Flammable. Keep away from heat, sparks and flame. Vapors can travel long distances and may ignite explosively. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation or by using explosion-proof exhaust fans both during and after application. **Vapor Harmful.** Do not breathe vapors or spray mist. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Wear a properly fitted organic vapor respirator (NIOSH/MSHA TC-23C or equivalent) until fumes are gone or leave the area. Close container after each use. Do not transfer contents to other containers for storage.

First Aid: In case of eye contact, flush with plenty of water for at least 15 minutes and get medical attention if irritation persists. For skin contact, wash with soap and water thoroughly. If affected by vapor inhalation, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get prompt medical attention. If swallowed, call physician immediately. Never give anything by mouth to an unconscious person. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.