



239 KEL-BOND II

Waterbase Surface Conditioner

Product Description

A lightly pigmented, water thinned surface conditioner for use on previously painted, lightly chalking surfaces. Good for commercial and residential application.

Performance Features

- Ties Down Light Chalk
- Superior Penetration
- Excellent Adhesion
- Easy Application
- Water Clean up

Product Specifications

Resin Type:	Alkyd modified latex
Color Range:	White
Drying Time: (75° F. & 50% R.H.)	To touch: 8 hours To recoat: 24 hours.
Practical Coverage:	Approx. 250-350 sq ft/gallon
Recommended Dry Film Thickness:	1.5-2.0 mils per coat
Weight Per Gallon:	9.5 lbs.
Solids By Weight:	40%
Solids By Volume:	32%
Shelf Life:	2 years (unopened containers)
Sizes:	One & five gallon containers
V.O.C.	<100 Grams per liter
Clean Up:	Water

Product Analysis (by weight)

PIGMENT COMPOSITION		16%
Titanium Dioxide:		6%
Silicate:		10%

VEHICLE COMPOSITION		84%
Latex Resins:		14%
Alkyd Resins:		7%
Linseed oil:		3%
Water, Surfactants, Defoamers:		60%

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, glazed or dense surfaces. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

Previously Painted Surfaces:

This product is not designed to eliminate required surface preparation. All peeling, flaking or moderate to heavy chalky surfaces must be removed to a firm, clean surface by sandblasting or other suitable means.

System Recommendations

Previously Painted Surfaces:

PRIMER: 239 Kel-Bond II

FINISH: Appropriate Kelly-Moore finish.

Application

Brush, roll or spray. Do not apply when material, air, and/or surface temperature is below 40°F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Continued Next Page

239 KEL-BOND II (cont.)

Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information, consult the Material Safety Data Sheet for this product..

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Mildew: This paint has been formulated to be mildew resistant, however, it will not mildew-proof the surface nor completely prevent or destroy mildew. Therefore, Kelly-Moore Paint Company Inc. assumes no responsibility for mildew development.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.