



343 KEL-PRO

Interior/Exterior Texture Paint

Product Description

An economical interior/exterior latex texture paint designed to provide a decorative and protective finish for primed or previously painted interior and exterior surfaces.

Performance Features

- Quick Drying
- Self-Sealing
- Can be applied by brush, roller or spray
- Water clean-up

Product Specifications

Resin Type:	Acrylic and Vinyl Acrylic
Pigment Type:	Titanium Dioxide, extender pigments, others for color
Color Range:	White & factory tinted colors White may be custom tinted
Finish:	Flat to Low Sheen (MPI Gloss Levels 1 & 2)
Drying Time: (75° f. & 50% r.h.)	To touch: 30 min. to 1 hour To recoat 2 to 4 hours.
Practical Coverage:	150-250 sq. ft. per gallon
Recommended Dry Film Thickness:	1.5 to 2.0 mils per coat
Weight per gallon:	9.6 lbs.
Solids by weight:	41%
Solids by volume:	27%
Sizes:	Five gallon containers
V.O.C.	<100 Grams per liter
Clean up:	Water

Product Analysis

This product is manufactured from a variety of virgin and post-manufacturing materials. It also contains a minimum of 10% post-consumer waste.

Surface Preparation

General: All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating.

System Recommendations

All bare or uncoated surfaces should be primed with a suitable primer.

FINISH: 343 Interior/Exterior Latex Paint

Application

Brush, roll or spray. Spray application requires 0.022 or larger spray nozzle and no filters in the gun or pump due to the texture. Do not apply when material, air, and/or surface temperature is below 50°F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Thinning

None required for normal environmental and application conditions.

Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN.

Warranty: This product is sold without warranty. Kelly-Moore Paint Company, Inc. and its distributors assume no responsibility express or implied for use of this product. Suitability of this product for any specific purpose must be determined by the user.