



57 TIMBER TONES

Semi-Transparent Exterior Alkyd Stain

THIS PRODUCT MAY NOT BE AVAILABLE IN SOME AREAS DUE TO VOC REGULATIONS
Contact your Kelly-Moore representative for more information

Product Description

A pigmented, oil based, penetrating, semi-transparent wood stain formulated to protect, color and enrich the natural beauty of new wood siding, trim, fences and other exterior wood surfaces. Tint before use, not recommended for use as a clear finish.

Performance Features

- Penetrates Wood
- Enhances Wood Grain
- Semi-Transparent Finish
- Wide Color Selection
- Easy Application

Product Specifications

Resin Type:	Alkyd & Linseed oil
Color Range:	Custom tints
Drying Time: (75° F. & 50% R.H.)	To touch: 6 hours.
Coverage:	Approx. 200-250 sq ft/gallon
Weight per Gallon:	7.2 lbs.
Solids by Weight:	37%
Solids by Volume:	32%
Shelf Life:	2 years (unopened containers)
Sizes:	Five gallon & one gallon
V.O.C.	<550 Grams per Liter
Clean Up:	Mineral Spirits

Product Analysis before tinting (by weight)

PIGMENT COMPOSITION	0%
VEHICLE COMPOSITION	100%
Alkyd Resin:	36%
Linseed Oil:	2%
Solvent, Driers, Additives :	62%

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All wood surfaces must be firm, dry and cleaned free of dust, dirt, oil, grease, wax, paint, pitch, sap, mildew or any other contamination or condition that would adversely affect the performance of the coating. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

System Recommendations

STAIN: 57 Timber Tones

Application

Brush, roll or spray. Spray application should be back brushed or rolled. Apply a full, even coat. Maintain a wet edge to avoid lap marks. Do not apply when material, air, and/or surface temperature is below 40°F. Stir thoroughly before and during use. Always test stain on wood to be stained prior to application. Semi-transparent stains vary significantly depending on color and porosity of substrate as well as application methods.

Thinning

This product has been formulated to comply with current regulations. DO NOT THIN.

Continued Next Page

57 TIMBER TONES (cont.)

Precautions

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE LIQUID AND VAPOR.

Contains Mineral Spirits. Vapor Harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. **Keep away from heat and flame.** Do not smoke. Prevent build up of vapors in enclosed areas by opening all windows and doors to achieve cross-ventilation during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Always wear respiratory protection during spray application. Close container after each use. Avoid contact with eyes and skin. First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If swallowed, get medical attention immediately. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.