

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name 925 Stain Lock Quick Dry Primer Sealer 100 White
Version # 01
Revision date 01-16-2011
CAS # Mixture
Product code 925-100
Product use Paint.
Manufacturer/Supplier Kelly-Moore Paint Co., Inc.
987 Commercial St., San Carlos, CA 94070
E-mail: rstetson@kellymoore.com
Telephone number: 1-800-874-4436
Contact Person: Robert Stetson

Emergency Emergency Telephone Number: 1-800-424-9300

2. Hazards Identification

Physical state Solid.
Appearance Milky white to colored liquid.
Emergency overview CAUTION

Combustible liquid and vapor.
Prolonged or repeated contact may dry skin and cause irritation.
This product is hazardous according to OSHA 29 CFR 1910.1200.

OSHA regulatory status

Potential health effects

Routes of exposure

Inhalation. Skin contact.

Eyes

Direct contact with eyes may cause temporary irritation.

Skin

Prolonged or repeated contact may dry skin and cause irritation.

Inhalation

Prolonged inhalation may be harmful.

Ingestion

Ingestion may cause irritation and malaise.

Target organs

Central nervous system. Skin.

Chronic effects

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

Signs and symptoms

Defatting of the skin. Vapors may cause drowsiness and dizziness.

Potential environmental effects

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Titanium dioxide	13463-67-7	<13
Distillates (petroleum), oxidized light	64742-98-9	<8
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	<5
Ligroine	8032-32-4	<3
Xylene	1330-20-7	<3
Solvent naphtha (petroleum), light aromatic	64742-95-6	<2
m-Xylene	108-38-3	<1.5
p-Xylene	106-42-3	<1

Composition comments

Components not listed are either non-hazardous or are below reportable limits. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

First aid procedures

Eye contact	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms persist.
Skin contact	Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. Get medical attention if irritation persists after washing.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention if any discomfort continues.
Ingestion	Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions.

Notes to physician

Treat symptomatically.

General advice

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Flammable properties

Combustible liquid and vapor.

Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Protection of firefighters

Protective equipment and precautions for firefighters Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions

Avoid inhalation of vapors and contact with skin and eyes. Wear appropriate personal protective equipment (See Section 8).

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for containment

Eliminate all ignition sources. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewer, basements or confined areas.

Methods for cleaning up

Should not be released into the environment.

Large Spills: Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the MSDS.

7. Handling and Storage

Handling

Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Storage

Keep away from heat, sparks, and flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from incompatible materials.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
m-Xylene (108-38-3)	STEL	150 ppm
	TWA	100 ppm
p-Xylene (106-42-3)	STEL	150 ppm
	TWA	100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Xylene (1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
m-Xylene (108-38-3)	PEL	435 mg/m3 100 ppm
p-Xylene (106-42-3)	PEL	100 ppm 435 mg/m3
Xylene (1330-20-7)	PEL	100 ppm 435 mg/m3

Engineering controls Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal protective equipment

Eye / face protection Wear approved safety goggles.

Skin protection Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Respiratory protection Use NIOSH certified, air purifying respirators with N-, P-, or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. protection provided by air-purifying respirators is limited. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134. Consult a qualified industrial hygienist or Safety Professional for respirator selection guidance.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance Milky white to colored liquid.

Color Various.

Odor Slightly ammoniacal.

Odor threshold Not available.

Physical state Solid.

Form Liquid.

pH Not available.

Melting point Not available.

Freezing point Not available.

Boiling point Not available.

Flash point 105 °F (40.6 °C)

Evaporation rate < 1 (n-BuAc=1)

Flammability limits in air, upper, % by volume Not available.

Flammability limits in air, lower, % by volume Not available.

Vapor pressure Not available.

Vapor density > 1 Air = 1

Specific gravity Not available.

Solubility (water) Moderately soluble

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.
Decomposition temperature Not available.

10. Chemical Stability & Reactivity Information

Chemical stability Material is stable under normal conditions.
Conditions to avoid Contact with incompatible materials. Keep away from heat, sparks, and flame.
Incompatible materials Strong oxidizing agents. Strong acids.
Hazardous decomposition products Carbon oxides. Silicon oxides.
Possibility of hazardous reactions Will not occur.

11. Toxicological Information

Acute effects In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Ingestion may cause irritation and malaise.
Sensitization Not a skin sensitizer.
Chronic effects Prolonged or repeated contact may dry skin and cause dermatitis. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.
Carcinogenicity Potentially carcinogenic components are typically only present in trace amounts. Due to the form of the product, exposure to the potentially carcinogenic components is not expected.

ACGIH Carcinogens

Crystalline silica (CAS 14808-60-7)	A2 Suspected human carcinogen.
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
m-Xylene (CAS 108-38-3)	A4 Not classifiable as a human carcinogen.
p-Xylene (CAS 106-42-3)	A4 Not classifiable as a human carcinogen.
Talc (CAS 14807-96-6)	A4 Not classifiable as a human carcinogen.
Titanium dioxide (CAS 13463-67-7)	A4 Not classifiable as a human carcinogen.
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (CAS 14808-60-7)	1 Carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
m-Xylene (CAS 108-38-3)	3 Not classifiable as to carcinogenicity to humans.
p-Xylene (CAS 106-42-3)	3 Not classifiable as to carcinogenicity to humans.
Silicon dioxide (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.
Talc (CAS 14807-96-6)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	3 Not classifiable as to carcinogenicity to humans.
Toluene (CAS 108-88-3)	2B Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

US NTP Report on Carcinogens: Known carcinogen

Crystalline silica (CAS 14808-60-7)	Known carcinogen.
-------------------------------------	-------------------

Further information Components of the product may be absorbed into the body through the skin.

12. Ecological Information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Environmental effects An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Persistence and degradability No data is available on the degradability of this product.
Bioaccumulation / Accumulation No data available.
Mobility in environmental media The product is miscible with water. May spread in water systems.
Partition coefficient (n-octanol/water) Not available.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 °F

US RCRA Hazardous Waste U List: Reference

m-Xylene (CAS 108-38-3)	U239
p-Xylene (CAS 106-42-3)	U239
Toluene (CAS 108-88-3)	U220
Xylene (CAS 1330-20-7)	U239

Disposal instructions Do not allow this material to drain into sewers/water supplies. This product, in its present state, when discarded or disposed of, may be a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

Waste from residues / unused products Dispose in accordance with applicable federal, state, and local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1263
Proper shipping name	Paint
Hazard class	Combustible Liquid
Labels required	3
Additional information:	
Special provisions	B1, B52, IB3, T2, TP1
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

Basic shipping requirements:

UN number	1263
Proper shipping name	Paint
Hazard class	3
Packing group	III
Additional information:	
ERG code	3L

IMDG

Basic shipping requirements:

UN number	1263
Proper shipping name	PAINT
Hazard class	3
Packing group	III
EmS No.	F-E, S-E*

15. Regulatory Information

US federal regulations This product is hazardous according to OSHA 29 CFR 1910.1200.

US TSCA Section 12(b) Export Notification: Export Notification requirement/De minimis concentration

p-Xylene (CAS 106-42-3)	1.0 % One-Time Export Notification only.
-------------------------	--

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Ethylbenzene (CAS 100-41-4)	0.1 %
m-Xylene (CAS 108-38-3)	1.0 %
p-Xylene (CAS 106-42-3)	1.0 %
Toluene (CAS 108-88-3)	1.0 %
Xylene (CAS 1330-20-7)	1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Ethylbenzene (CAS 100-41-4)	Listed.
m-Xylene (CAS 108-38-3)	Listed.

p-Xylene (CAS 106-42-3)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

CERCLA (Superfund) reportable quantity (lbs)

Xylene 1000
m-Xylene 1000
p-Xylene 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Ethylbenzene (CAS 100-41-4)	Listed.
m-Xylene (CAS 108-38-3)	Listed.
p-Xylene (CAS 106-42-3)	Listed.
Silicon dioxide (CAS 7631-86-9)	Listed.
Talc (CAS 14807-96-6)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline silica (CAS 14808-60-7)	Listed: October 1, 1988 Carcinogenic.
Ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004 Carcinogenic.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)	Listed: January 1, 1991 Developmental toxin.
------------------------	--

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)	Listed: August 7, 2009 Female reproductive toxin.
------------------------	---

US - Massachusetts RTK - Substance: Listed substance

Crystalline silica (CAS 14808-60-7)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Limestone (CAS 1317-65-3)	Listed.
m-Xylene (CAS 108-38-3)	Listed.
p-Xylene (CAS 106-42-3)	Listed.
Silicon dioxide (CAS 7631-86-9)	Listed.
Talc (CAS 14807-96-6)	Listed.
Titanium dioxide (CAS 13463-67-7)	Listed.

Toluene (CAS 108-88-3) Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Ethylbenzene (CAS 100-41-4) 500 LBS
m-Xylene (CAS 108-38-3) 500 LBS
p-Xylene (CAS 106-42-3) 500 LBS
Toluene (CAS 108-88-3) 500 LBS
Xylene (CAS 1330-20-7) 500 LBS

US - New Jersey RTK - Substances: Listed substance

Crystalline silica (CAS 14808-60-7) Listed.
Ethylbenzene (CAS 100-41-4) Listed.
Ligroine (CAS 8032-32-4) Listed.
m-Xylene (CAS 108-38-3) Listed.
p-Xylene (CAS 106-42-3) Listed.
Silicon dioxide (CAS 7631-86-9) Listed.
Talc (CAS 14807-96-6) Listed.
Titanium dioxide (CAS 13463-67-7) Listed.
Toluene (CAS 108-88-3) Listed.
Xylene (CAS 1330-20-7) Listed.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Crystalline silica (CAS 14808-60-7) Listed.
Ethylbenzene (CAS 100-41-4) Listed.
Ligroine (CAS 8032-32-4) Listed.
Limestone (CAS 1317-65-3) Listed.
m-Xylene (CAS 108-38-3) Listed.
p-Xylene (CAS 106-42-3) Listed.
Silicon dioxide (CAS 7631-86-9) Listed.
Talc (CAS 14807-96-6) Listed.
Titanium dioxide (CAS 13463-67-7) Listed.
Toluene (CAS 108-88-3) Listed.
Xylene (CAS 1330-20-7) Listed.

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 2
Physical hazard: 0

NFPA ratings

Health: 0
Flammability: 2
Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Additional information is given in the Material Safety Data Sheet.

Issue date

01-16-2011