



925 STAIN LOCK

Quick Dry Primer Sealer

Product Description

A professional quality, interior quick dry synthetic primer-sealer. Features good sealing properties and fast recoat time. Good for commercial and residential application.

Performance Features

- Excellent Enamel Holdout
- Seals in Stains
- Excellent Adhesion
- Good Flow & Leveling
- Fast Drying

Product Specifications

Resin Type:	Synthetic
Color Range:	Off White
Drying Time: (75° F. & 50% R.H.)	To touch: 30 minutes To recoat 1 hour Overnight dry is recommended for water stains.
Practical Coverage:	Approx. 450-550 sq ft/gallon
Recommended Dry Film Thickness:	1.5-2.0 mils per coat
Weight Per Gallon:	12.4 lbs.
Solids By Weight:	77%
Solids By Volume:	57%
Shelf Life:	2 years (unopened containers)
Sizes:	One & five gallon containers
V.O.C.	<350 Grams per liter
Clean Up:	Mineral Spirits

Product Analysis (by weight)

PIGMENT COMPOSITION	58%
Titanium Dioxide:	14%
Silicates:	26%
Calcium Carbonate:	18%
VEHICLE COMPOSITION	42%
Synthetic Resin:	19%
Solvents, Driers, Additives::	23%

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalky or loose paint, rust, loose mill scale, bond breakers and curing compounds, efflorescence, asphalt stains, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, glazed or dense surfaces. Fill holes and surfaces irregularities with a suitable patching compound to match the surface profile.

System Recommendations

Wallboard, Wood, Hardboard:

PRIMER: 925 Stain Lock Quick Dry
Primer Sealer

FINISH: Appropriate wall, trim or ceiling
paint.

Application

Spray application is recommended for large areas. Small areas may be brushed or rolled. Maintain a wet edge to avoid lap marks. Do not apply when material, air, and/or surface temperature is below 40°F. Stir thoroughly before and during use.

Thinning

This product has been formulated to comply with current regulations. **DO NOT THIN.**

Continued Next Page

925 STAIN LOCK (cont.)

Precautions

WARNING! FLAMMABLE LIQUID AND VAPOR

Contains Petroleum Distillates and Xylene. Flammable. Keep away from heat, sparks and flame. Vapors can travel long distances and may ignite explosively and cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation or by using explosion-proof exhaust fans both during and after application. **Vapor Harmful.** Do not breathe vapors or spray mist. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Wear a properly fitted organic vapor respirator (NIOSH/MSHA TC-23C or equivalent) until fumes are gone or leave the area. Close container after each use. Do not transfer contents to other containers for storage. **First Aid:** In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists. For skin contact, wash with soap and water thoroughly. If affected by vapor inhalation, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get prompt medical attention. If swallowed, call physician immediately. Never give anything by mouth to an unconscious person. **Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.