



973 ACRY-PLEX

— Zero VOC —

Interior Wall Primer & Undercoat

Product Description

Acry-Plex Interior Wall Primer & Undercoat is a premium, zero V.O.C., low odor, acrylic drywall primer and enamel undercoat for interior wood, drywall and cured concrete and plaster surfaces. Contains a tannin blocking agent to prevent tannin staining on cedar, redwood, red pine and other tannin rich woods. Ideal for occupied areas or anywhere odor is a concern.

Compliance - Performance - Certification

- ✓ MPI Approved Product List: #50
- ✓ Meets MPI GPS-1 & GPS-2
- ✓ Meets Green Seal GS-11 VOC Limits
- ✓ Meets LEED EQ Credit 4.2 VOC Limits
- ✓ CHPS Indoor Advantage Gold Certified
- ✓ Green Wise Certified
- ✓ Meets CARB VOC Limits
- ✓ Meets SCAQMD VOC Limits
- ✓ Meets National AIM VOC Limits

Performance Features

- Excellent enamel holdout
- Easy Sanding
- Good Hide
- Low Odor and VOC
- Resists Tannin Stains
- Fast Drying
- Easy Soap & Water Clean Up

Product Specifications

Resin Type:	Acrylic
Color Range:	White
Drying Time: (75° F. & 50% R.H.)	To touch: 1 hour To recoat 4 hours.
Practical coverage:	Approx. 250-350 sq ft/gallon
Recommended Dry Film Thickness:	1.5-2.0 mils per coat
Weight per Gallon:	11.1 lbs.
Solids by Weight:	50%
Solids by Volume:	34%
Shelf Life:	2 years (unopened containers)
Sizes:	One & five gallon containers
V.O.C.	0 Grams per liter
Clean Up:	Water

Product Analysis (by weight)

PIGMENT COMPOSITION		34%
Titanium Dioxide:		14%
Calcium Carbonate:		13%
Silicates:		7%

VEHICLE COMPOSITION		66%
Acrylic Resin:		15%
Water, Surfactants, Defoamers:		51%

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

General:

All surfaces must be cured, firm, dry and cleaned free of dust, dirt, oil, grease, wax, chalk, mildew or any other contamination or condition that would adversely affect the performance of the coating. Sand glossy, dense or glazed surfaces.

System Recommendations

Wallboard, Plaster, Concrete, & Wood:

PRIMER: 973 Acry-Plex 100% Acrylic
Interior Enamel Undercoat

FINISH: Appropriate finish.



Application: Brush, roll or spray.

Do not apply when material, air, and/or surface temperature is below 50°F. Stir thoroughly before and during use. Maintain a wet edge to avoid lap marks.

Thinning

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon.

Continued Next Page

973 ACRY-PLEX (cont.)

Precautions

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. Protect from freezing. For additional safety information, consult the Material Safety Data Sheet for this product..

USE ONLY WITH ADEQUATE VENTILATION.
KEEP OUT OF REACH OF CHILDREN.

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.