

THIS PRODUCT MAY NOT BE AVAILABLE IN SOME AREAS DUE TO VOC REGULATIONS
Contact your Kelly-Moore representative for more information

Product Description

A one component, solvent borne, high gloss, clear acrylic sealer designed for use on concrete, masonry, and brick. Dustproofs concrete by penetrating surface pores leaving a tough, durable film.

Performance Features

- Non-Yellowing
- Excellent Adhesion to Concrete
- Good Water & Salt Chemical Resistance
- Good Abrasion Resistance
- Can be Sprayed, Padded or Rolled

Product Specifications

Resin Type	Acrylic
Color Range	Clear
Finish	High Gloss
Drying Time	8 hours to recoat
Practical Coverage	250-450 Sq. Ft. / Gallon
Recommended Dry Film Thickness	1.2 - 2.2 mils per coat
Solids By Volume	35%
Sizes	Five gallon pails
V.O.C.	560 Grams per liter
Clean Up	KM-S-74 or KM-SA-50

Surface Preparation

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Surface Preparation:

Remove all dirt, grease, oil, soil, chemical contaminants, and other matter. Allow surface to dry.

Application Procedure:

When mixing, use an EXPLOSION PROOF SLOW SPEED DRILL WITH A JIFFY MIXER. Apply a uniform wet film, do not puddle material. Do not cover more area than can be worked in 10 minutes due to fast dry time. When spraying, use a low pressure machine. Two coats may be necessary depending on porosity or type of service.

For safety and product curing, proper ventilation is necessary throughout application and cure.

Dry Times: 8 hours

See Precautions and Limited Warranty next page

KM-669 (cont.)

Precautions

KM-669 is Flammable. KM-669 contains flammable solvents. Keep away from all sources of ignition during mixing, application, and cure. In confined areas, provide adequate forced air ventilation. The use of goggles, fresh air masks or NIOSH approved respirators, protective skin cream and protective clothing is a recommended standard practice when spraying coatings

Proper Disposal

For proper disposal of excess material, please contact your local city or county waste management agency.

Limited Warranty: The statements made on this bulletin, product labels or by any of our agents concerning this material are given for information only. They are believed to be true and accurate and are intended to provide a guide to approved construction practices and materials. As workmanship, weather, construction equipment, quality of other materials and other variables affecting results are all beyond our control, Kelly-Moore Paint Company, Inc., does not make nor does it authorize any agent or representative to make any warranty of MERCHANTABILITY OR FITNESS for any purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material except that it conforms to Kelly-Moore's quality control standards. Any liability whatsoever of Kelly-Moore Paint Company, Inc. to the buyer or user of this product is limited to the purchaser's cost of the product itself.

**SEE MATERIAL SAFETY DATA SHEETS FOR
FULL SAFETY PRECAUTIONS.**

KM-669 IS FOR PROFESSIONAL USE ONLY

KM-669 IS FOR INDUSTRIAL USE ONLY

KEEP AWAY FROM CHILDREN