

**MATERIAL SAFETY DATA SHEET**  
**For Coatings Resins & Related Materials**

===== **Section I** =====

Manufactured For: Kelly-Moore Paints  
Address: 987 Commercial Street  
San Carlos, CA 94070

Prep Date: 07/27/06

Emergencies Involving Spills, Leaks,  
Fires, Exposure, Or Accident Contact  
Chemtrec: 1-800-424-9300

Product Class: Epoxy Coating  
Trade Name: **KM-280-811 TINT BASE PART A BASE**  
H.M.I.S. Codes: H F R P  
2\* 3 0 -

Information Phone: 1-888-677-2468

===== **Section II - HAZARDOUS INGREDIENTS** =====

Ingredient	C.A.S.#	Weight Percent	Occup. Exposure Limits		Vapor Pressure	
			OSHA PEL	ACGIH TLV	mm Hg	& Temp.F
Epoxy Resins	Mixture	24-30	Not Established		Not Determined	
*Xylene	1330-20-7	8-12	100 ppm	100 ppm	5.1	68
*Ethyl Benzene	100-41-7	0-3	100 ppm	100 ppm	7.1	68
PM Acetate	108-65-6	8-12	Not Established		<1	68
Nonyl Phenol	25154-52-3	6-8	Not Established		<1	68

\*Indicates toxic chemical(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372.

===== **Section III - PHYSICAL DATA** =====

Boiling Range (Deg. F): 220°  
Evaporation Rate: Slower than Ether  
Percent Volatile By Volume: 34

Vapor Density: Heavier than air

Weight Per Gallon (lbs.): 12.3 ± .2

===== **Section IV - FIRE & EXPLOSION HAZARD DATA** =====

Flash Point (Deg. F): 80°  
Extinguishing Media: Foam, alcohol foam, CO2, dry chemical, water spray

Lower Explosive Limit: 1.0

OSHA Flammability Classification: Flammable Liquid IC

Special Firefighting Procedures: Wear a NIOSH/MSHA approved self contained breathing apparatus and full protective clothing. Use water to keep fire exposed containers cool.

Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation to ignition sources at locations distant from material handling point. Pressure may build up in containers and create an explosion hazard.

**KM-280-811 TINT BASE PART A BASE**

**=====  
Section V - HEALTH HAZARD DATA  
=====**

**THIS PRODUCT IS FLAMMABLE**

**Effects Of Overexposure:**

**Eyes:** Irritation, burning, tearing and redness.

**Skin:** Moderate irritation or defatting of skin upon prolonged or repeated contact.

**Ingestion:** Abdominal pain, nausea, vomiting and diarrhea.

**Inhalation:** Excessive exposure to vapors can cause headache, dizziness, uncoordination, nausea and loss of consciousness.

**Emergency & First Aid Procedures:**

**Eyes:** Flush with water for 15 minutes.

**Skin:** Remove contaminated clothing, wash skin with soap and water.

**Ingestion:** Do not induce vomiting. Get medical attention immediately.

**Inhalation:** Move to fresh air, aid breathing if necessary.

In all cases, consult a physician for best treatment.

Chemical listed as carcinogen or potential carcinogen:

NTP: No      IARC: No      OSHA: No

**=====  
Section VI - REACTIVITY DATA  
=====**

**Stability:** Product Stable

**Conditions to Avoid:** All sources of ignition

**Incompatibility (Materials to Avoid):** Oxidizing agents, strong acids & bases

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, nitrogen oxides and organic compounds.

**Hazardous Polymerization:** Will Not Occur

**=====  
Section VII - SPILL OR LEAK PROCEDURES  
=====**

Steps To Be Taken In Case Material Is Released Or Spilled: Dike spill area. Absorb spill with inert absorbent material. Place in sealed metal containers for proper disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

**=====  
Section VIII - SPECIAL PROTECTION INFORMATION  
=====**

**Respiratory Protection:** Use a NIOSH/MSHA jointly approved respirator

**Ventilation:** Use mechanical ventilation

**Protective Gloves:** Neoprene or rubber

**Eye Protection:** Chemical splash goggles

**Other Protective Equipment:** Protective clothing, barrier cream, eye bath, safety shower

**=====  
Section IX - SPECIAL PRECAUTIONS  
=====**

Precautions To Be Taken In Handling & Storing; Store in dry area. Keep away from open flames and high temperatures.

Other Precautions: Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.

**State and Local Regulations**

California Proposition 65

This product contains the following substances known to the State of California to cause cancer, birth defects or other reproductive hazards: Benzene, Toluene.